




FS Casale

Porcelain tiles

FS CASALE | FS CASALE



FS CASALE



10 patterns

45,2 * 45,2 * 1 cm | 16 5/8 * 16 5/8 * 3/8"

NO RECTIFIED	NATURAL PRICE CODE BN61
FS CASALE	21077

CARACTERÍSTICAS TÉCNICAS TECHNICAL CHARACTERISTICS		
joint 	versatile 	matt 
diferent shades 	shade variation 	various graphics 

CARACTERÍSTICAS TECNICAS ANTIDESLIZAMIENTO ANTI-SLIP CHARACTERISTICS		
Ensayo Essay	Características Features	Resultado Result
DIN 51130	Ángulo crítico (Pies calzados) Critical angle (footwear)	R10
DIN 51097	Ángulo crítico (Pies descalzos) Critical angle (Wet loaded barefoot)	-
BS-7976-2	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test)	+36Wet
UNE-ENV-12633	Antideslizamiento (Test del péndulo) Slip resistance (Pendulum test)	Class 2
ANSI A.1371:2012	Coeeficiente de Fricción Dinámico Dynamic Coefficient of Friction (DCOF)	> 0,42
ISO 10545-7	Resistencia a la Abrasión Superficial/ Resistance to Surface Abrasion	PEI 4

EMBALAJE PACKING									
Formato Sizes		Cajas Boxes			Pallet			Cont./20'	Cont./20'
cm		Piezas	m²/ sq.m	kg	Cajas	m²/ sq.m	kg	Tamaño cm aprox.	m²/ sq.m
45,2 * 45,2 * 1		5	1,02	23,70	66	67,42	1589,20	120 * 80 * 105	912,12
inch		Units	ft²	lb	Boxes	ft²	lb	Sizes inch approx.	ft²
16 5/8 * 16 5/8 * 3/8		5	11,00	52,14	66	725,71	3496,24	47 1/4 * 31 1/2 * 41 5/16	10959,56